


SAFETY REGULATION VV 06 Working with aerial work platform or scissor lift	
--	---

Date of last change	19/04/2022
Nature of last modification	Review

1	PURPOSE	2
2	SCOPE	2
3	DEFINITIONS.....	2
4	PRESCRIPTION	2
4.1	Requirements for use of the aerial work platform or scissor lift..	2
4.2	Requirements when allowing an aerial work platform or scissor lift	2
4.3	Measures in the event of defects or maintenance of a cherry picker/scissor lift	3

SAFETY REQUIREMENT VV06

Working with aerial work platform or scissor lift



Balen/Pelt

1 PURPOSE

In order to control the risks associated with the use of aerial work platforms or scissor lifts, in addition to the facilities as described in the legislation, NYRSTAR Balen/Pelt in this safety requirement has laid down and further developed additional rules and measures. These are included in this regulation.

2 SCOPE

The requirements of this safety regulation apply to Nyrstar Belgium's premises

3 DEFINITIONS

A cherry picker/aerial work platform or scissor lift is a work platform that can be raised, this is done by a lifting mechanism, in a arms or scissor construction.

4 PRESCRIPTION

4.1 Requirements for use of the aerial work platform or scissor lift

The following requirements apply:

- Prior to commissioning, the user (executor) must carry out a check. He must check the points included in form [XF-452-FCH-0-00006](#) Aerial work platform/scissor lift: check before commissioning. This form includes all requirements for the aerial work platform or scissor lift and for the user(s). In the event that one or more of the conditions are not met, the aerial work platform may not be used. Testing of an aerial work platform is only possible in a completely free safe environment
- As soon as work conditions occur during use that lead to one or more conditions from the checklist no longer being met, the work must be interrupted. The work may only be resumed when all conditions have been met again.
- It is not permitted to leave the work bucket of the aerial work platform when the work bucket is in an aerial position. Exceptions to this are permitted if a Task Risk Analysis associated with that work describes how the risk of falling is overcome and these provisions are strictly observed in the implementation. There must be no connection between the aerial work platform and the double catch line on exit

4.2 Requirements when allowing an aerial work platform or scissor lift

When admitting a cherry picker or scissor lift to the Nyrstar Belgium site, the gatekeepers department/O&V Department checks the following points:

- Validity of the last inspection and the presence of the inspection report this does not have to be the entire report but the results of the most important safety findings (e.g. approval or rejection))

SAFETY REQUIREMENT VV06

Working with aerial work platform or scissor lift



Balen/Pelt

4.3 Measures in the event of defects or maintenance of a cherry picker/scissor lift

- **IN CASE OF DEFECTS:** Relocate a defective aerial work platform on its own requires a documented risk analysis. Testing a defective aerial work platform is only possible in a completely free safe environment.
- **MAINTENANCE:** maintenance may only be carried out in a safe environment and under no circumstances on site.